



PCB LAYOUT

目录 MAPX	设定内容 MODIFICATION	日期 DATE
------------	----------------------	------------

特性: Specifications:

电气: Electrical:

1. 接触阻抗: Contact Resistance:
30 milliohms MAX
2. 耐电压: Dielectric With Standing Voltage:
500 V AC AT Sea Level
3. 绝缘阻抗: Insulation Resistance:
1000 MEGA ohms MIN

机构: Mechanical:

1. 结合力: Mating Force:
35 N MAX 最大 35 N
2. 拔出力: Unmating Force:
8 N MIN 最少 8 N

材料: Material:

1. 塑胶: PBT.
 2. 端子: Contact: C2680
 3. 外壳: Shell: SPCC
- 电镀: Finish:
1. 端子: Contact: Plated Gold in Mating Area:
Tin/Lead On Solder Tails. 接触点镀金, 脚镀锡
 2. 外壳: Shell:
Nickel Plating . 镀镍

额定电流1. 5A, 盐雾24H, 镀锡部分12H

产品图 PRODUCT CHART DWG		深圳市金航标电子有限公司		WWW.BDS666.COM	
公差表 TOLERANCE UNLESS OTHERWISE		单位 UNITS	制图 DRAWING	客户料号 PRODUCT PART NO.	0755-83044319
X	±0.30	MM	审核 CHKD	产品名称 PRODUCT NAME	90° 外打C款铁直弯直脚短弹
X	±0.25		日期 DATE	角法 ANGLE	版本 VER
XX	±0.20		2014/04/23	核准 APPD	A0
未标注的公差按一般标准计算					