



2~5A

SPECIFICATIONS

- 1、Current Rating: 3A AC, DC
- 2、Voltage Rating: 250V AC, DC
- 3、Temperatuer Range: $-25^{\circ}\text{C} \sim +85^{\circ}\text{C}$
- 4、Contact Resistance: $20\text{m}\Omega$ Max
- 5、Insulation Resistance: $1000\text{M}\Omega$ Min
- 6、Withstanding Voltang: 1000V AC/minute
- 7、Material: Wafer Nylon46, UL94V-0
PIN Brass Tin-plated

| 编 号 | 尺寸 (mm) | |
|------------|---------|-------|
| | A | B |
| A2508-02AW | 2.50 | 7.50 |
| A2508-03AW | 5.00 | 10.00 |
| A2508-04AW | 7.50 | 12.50 |
| A2508-05AW | 10.00 | 15.00 |
| A2508-06AW | 12.50 | 17.50 |
| A2508-07AW | 15.00 | 20.00 |
| A2508-08AW | 17.50 | 22.50 |
| A2508-09AW | 20.00 | 25.00 |
| A2508-10AW | 22.50 | 27.50 |
| A2508-11AW | 25.00 | 30.00 |
| A2508-12AW | 27.50 | 32.50 |
| A2508-20AW | 47.50 | 52.50 |

PCB LAYOUT

| | | | | | | | | | |
|-------------------|------------|----------|------------|-------|---------------|----------------|---------------------|-------|-----|
| GENERAL TOLERANCE | | 制图 | 钱岳生 | | 料号 | A2508-nAW | | 版本 | A |
| X.±0.25 | X.*±2' | DRAWING | 2013、07、01 | | PART NO. | XA-AW | | REV. | |
| .X±0.20 | .X*±1' | 审核 | 张名 | | 品名 | WAFER DIP TYPE | | 页次 | 1/1 |
| .XX±0.15 | .XX*±0.5' | CHECK | 2013、07、03 | | TITLE | | | SHEET | |
| .XXX±0.10 | .XXX*±0.5' | 核准 | 张名 | | 客户料号 | | | | |
| | | APPROVAL | 2013、07、03 | | CUTM. NO. | | | | |
| | | 单位 | MM | 比例 | 深圳市金航标电子有限公司 | | www.kinghelm.com.cn | | |
| | | UNITS | MM | SCALE | KH-A2508-13AW | | 0755-28190160 | | |