Kinghelm®

REVISIONS					
REV	NUMBER	DESCRIPTION	DWN	CHK	DATE
A		DESIGN			



NOTES:

1. ELECTRICAL:
1.1. VOLTAGE RATING:DCV 300V 10MS
1.2. CONDUCTANCE RESISTANCE: 3.0 OHM/MAX.
1.3. INSULATION RESISTANCE: 5.0M OHM/MIN.
1.4. THE CABLE SHOULD BE 100% ELECTRICAL TEST
1.5. IT SHOULD BE NO ANY OPEN/SHORT, MISWIRING AND INTERMITTENT FAILURES
2. MATERIAL:
2.1. SEE TABLE
3. ALL COMPONENTS ARE RoHS COMPLIANT.

ITEM NO.	PART NUMBER	DESCRIPITION	QTY.
②	接头	四代IPEX端子	1
①	同轴线	RG0.81红色线，OD:0.81MM	AS

深圳市金航标电子有限公司	www.kinghelm.com.cn
KH-IPEX4-221-RG0.81-R250	0755-28190160

ALL DIMENSION ARE IN MM	DRAWN Jamy	DATE 2020-06-15
	ENG.	
COMPUTER GENERATED IN SOLIDWORKS	MFG.	
DO NOT SCALE THIS DRAWING	Q.A.	
PROJECTION	GENERAL TOLERANCE FOR ANGLES X.X ± 1° X.XX ± 0.3 X.XXX ± 0.25 ± 0.150	

四代IPEX TO OPEN RG0.81红色转接线

CUSTOMER P/N:

SIZE	Number	REV
B		A
SCALE: Free	TYPE	SHEET 1 OF 1